

## SFace900



## ➔ Multi-Biometric Time Attendance and Access Control System

Face capacity : 1,200 (1:N), 3,000 (1:1)  
Fingerprint capacity : 2000 (Optimal 4000)  
ID Card capacity : 10,000 (Optional)  
Logs capacity : 100,000  
Display : 4.3-Inch Touch Screen  
Communication : TCP/IP, RS232/485, USB Host  
Standard Functions : Automatic Status Switch,  
Self-Service Query, Work Code, SMS DST,  
T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID  
Interfaces for : 3rd Party Electric Lock, Door Sensor,  
Exit Button, Alarm  
Wiegand Signal : Output  
Optional Functions : ID/MiFare Card, Wi-Fi, 3G,  
ADMS, 200 mAH Backup Battery  
Power Supply :12V 3A  
Operating Temperature : 0°C to 45°C

Operating Humidity : 20% - 80%  
Dimensions : 195.5x166.5x120mm (LxWxT)  
Package Weight : 1.6 kg

### Features :

- ▶ 1,200 face and 2,000 fingerprint templates
- ▶ Multi-languages
- ▶ High verification speed
- ▶ Optional built-in battery backup, providing approximately 4 hours of continuous operation
- ▶ One face template is registered for one user only
- ▶ Able to detect whether the face is an actual face or a photo, enhancing the security level of verification
- ▶ Outside installation (maximum 12,000 lux)