



SA42

Standalone touch keypad Access Control

Specifications

Card Type	Proximity
Working Voltage	DC12V
Reading Range	2-5 cm
Operating Humidity	10% - 90%
Door opening time	0 ~ 99s
Alarm output load	<= 2A
Idle Current	<= 30mA
Operating Temperature	-10 ~ 60°C
Lock output load	<= 1A
Short-circuit protect	<= 100us
Dimension (L*H*W)	75 x 113 x 15 mm



Features

Backlight touch keypad

Wg26 Input/Output

2000 cards/password in total

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by    

www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control

Specifications

Card Type	Proximity
Working Voltage	DC12V
Reading Range	2-5 cm
Operating Humidity	10% - 90%
Door opening time	0 ~ 99s
Alarm output load	$\leq 2A$
Idle Current	$\leq 30mA$
Operating Temperature	-10 ~ 60°C
Lock output load	$\leq 1A$
Short-circuit protect	$\leq 100\mu s$
Dimension (L*H*W)	75 x 113 x 15 mm