



V-AX11

DURABLE & SHOCK PROOF



Finger



RFID



WiFi



LAN



USB



Access Control



SSR

Fingerprint Time Attendance & Access Control System

Storage Capacity

Finger Capacity	10,000
Card Capacity	10,000
Max User	10,000
Password	10,000
Log Capacity	1,00,000

Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



V-AX11

Communication Interface

Communication	WiFi, TCP/IP, Rs485
	USB Host & Client

Biometric

Push Data	YES
Sensor	500 DPI
FAR	0.00001%
FRR	0.001%
Verification time	<=1 second
RF card options	Mifare Card (Optional)

Audio/Visual

LCD	Three-color indicator light
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Relay	YES
Support	V-R12

Power & Environment

Operating Temperature	-20°C ~ 50°C
Power	DC 12V, 2Amp
Dimension	204x139x38mm



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Compact & lightweight design



Unaffected by High Temperatures -20°C ~ 50°C

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service







Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by   CE FC

www.biomaxsecurity.com

Connect with us on

 BiomaxOfficial  BioMax Security
 biomaxsecurity  BioMax Access Control