

V-AX16

SIMPLICITY MEETS SMARTNESS



Finger



Password



Mini USB



LAN



Access Control

Outdoor Fingerprint Time Attendance & Access Control System

Storage Capacity

Finger Capacity	1000
Max User	1000
Password	1000
Log Capacity	50,000

Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Comprehensive software development kit(SDK) is available for development and integration.



V-AX16

Communication Interface

Communication	TCP/IP, RS485,USB
---------------	-------------------

Biometric

Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
Verification time	<=1 second

Audio/Visual

Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Relay out	YES
Anti Passback	YES

Power & Environment

Operating Temperature	-20°C ~ 50°C
Power	DC 12V
Dimension	80 x 180 x 40mm



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Compact & lightweight design



Unaffected by High Temperatures -20°C ~ 50°C

Software

Desktop



Time Attendance



Access Control



Employee Self Service







Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by    

www.biomaxsecurity.com

Connect with us on

 BiomaxOfficial  BioMax Security
 biomaxsecurity  BioMax Access Control