

CP- UNR-4K4324-V2**32 Ch. H.265 4K Network Video Recorder****Main Features**

- Up to 32 channel IP camera input
- H.265/H.264 dual codec decoding
- Up to 8Mp resolution preview and playback
- Max 200Mbps incoming bandwidth
- Support 4 SATA HDDs up to 24TB, 2 USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-4K4324-V2**32 Ch. H.265 4K Network Video Recorder****Feature**

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Record Interval
Max User Account
Ethernet
Protocols
Power Supply

Specification

Dual-core embedded processor
Embedded LINUX
32 channel
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
H.265/H.264
3840×2160, 1920×1080, 1280×1024, 1280×720, 1024×768
Max 200Mbps
1/4/8/9/16
MD Zones: 396(22×18).
Supports
Supports
16 Channel, Low Level Effective, Green Terminal Interface
4 Channel, NO/NC Programmable, Green Terminal Interface
iPhone, iPad, Android Phone
4 SATA III ports, up to 24TB
Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device/Network
1 HDMI, 1 VGA, 2 USB (1USB 3.0), 1 RS485, 1 RS232, 1 RJ45
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
1 RJ-45 port (10/100/1000Mbps), 1 Independent 1000Mbps Ethernet Port
HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, IP Search, ONVIF 2.4, CGI Conformant
AC 100~240V, 50/60 Hz

CP- UNR-4K4324-V2**32 Ch. H.265 4K Network Video Recorder****Feature**

Power Consumption

Working Temp

Dimensions

Weight

Specification

<13.7W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

440mm x 411.1mm x 76mm

4.7kg (without HDD)