

**CP- UVR-0401E1S-V4****4 Ch. 1080P Lite Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 2MP IP Camera
- All channel 1080P Lite Realtime Recording
- Support 1 SATA HDD up to 8TB, 2 USB Ports(2.0)
- HDMI / VGA Simultaneous Video Output
- H.264 dual-stream Video Compression
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



**CP-UVR-0401E1S-V4****4 Ch. 1080P Lite Cosmic HD DVR****Feature**

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
Video Input  
Video Output  
Compression  
Video Resolution

Video Recording

Video Display Split

Audio Input

Audio Output

Motion Detection

Video Loss

Camera Blank

Smart Phone

Hard Disk

Trigger Events

Recording Mode

Search Mode

Playback

Backup Mode

Interface Ports

Max User Account

Record Interval

Ethernet

**Specification**

Embedded processor

4+1 Ch. each channel up to 2MP

Embedded LINUX

Reuse audio in/out, RCA

GUI

4 channel, BNC

1 HDMI, 1 VGA

H.264

1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768

Main Stream: 1080N/ 720P/ 960H/ D1/ HD1/ BCIF/ CIF/ QCIF (1~25/30fps), Sub stream: CIF/ QCIF(1~15fps)

1/4/6

1 channel, RCA

1 channel, RCA

Supports

Supports

Supports

iPhone, iPad, Android Phone

1 SATA port, up to 8TB

Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips

Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop

Time /Date, Alarm, MD and Exact Search (accurate to second)

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom

USB Device/Network

1 HDMI, 1 VGA, 2 USB Ports(2.0)

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

RJ-45 port (10/100M)



# CP- UVR-0401E1S-V4

## 4 Ch. 1080P Lite Cosmic HD DVR



### Feature

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

### Specification

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, ONVIF Version 2.4 conformance

DC12V/2A

<10W (Without HDD)

-10°C ~ +55°C/ 0 ~ 90% RH

205mm x 211mm x 45mm

0.55kg (without HDD)



\*Product casing and specifications are subject to change without prior notice