



UHF 1-10 / 2-10

➔ UHF 1-10 / 2-10 : UHF RFID Reader

Dimension : 445 x 445 x 70(mm)
Reading Distance : Up to 12 meters (adjustable)
Communication Interface : Wiegand 34(Default) /
Wiegand 26, USB
Frequency : 902Mhz–928Mhz, 865MHz–868MHz
Shell Material : Die-casting aluminum shell,
Antenna panel with engineering plastics
Voltage : 9~12V DC
Temperature : -20°C to 60°C
Interface Protocol : EPC global UHF Class
1Gen 2/ISO 18000-6c
Multiple Tags Identification : >50
Multiple Tags Identification Speed : >50 Per second
Working Mode : Always read/Trigger read
I/O : Interface Supports external trigger
Maximum power consumption : <3W
(RF output 26dBm,multiple tags),
<2W (RF output 26dBm,Sigle tags)

Feature:

- ▶ Read range up to 12 meters (adjustable)
- ▶ Read Sensitivity: Line polarization read mode
- ▶ Wiegand 34-Bit (Can change to 26-Bit via software)
- ▶ Two working mode: Trigger read & Always read
- ▶ Comes with the mounting plate
- ▶ Weatherproof (IP66)
- ▶ Maximum Cable Distance: 100m
- ▶ Multiple label recognition