

# COSEC ARC DC200P

Two Door Controller with PoE+, Wi-Fi and Bluetooth



## GENERAL

Maximum Readers	Up to 2 Readers (Wiegand and/or RS-485)
Maximum Doors	2
Maximum Users	50,000
Event Buffer	500,000

## COMMUNICATION

Ethernet	Yes, 10/100 Mbps
RS-485	Yes
SSL Enabled	Yes
Bluetooth	Yes (BLE-10m)
Wi-Fi	Yes
PoE+	Yes, IEEE 802.3 af/at

## OPERATION MODES

Direct Door Mode	With COSEC CENTRA (with COSEC PANEL LITE V2 for Dual Door Mode)
Panel Door Mode	With COSEC PANEL

## READERS

Reader Power Output	Max. 12V DC @ 0.250A
Reader Types	2 Reader Port for any Wiegand or Matrix Reader
Interface	RS-485 (For Matrix Reader Only) and Wiegand IN

## IN/OUT PORTS

Exit Switch Port	Yes
Door Status Sense	Programmable NO, NC
Door Lock Relay	Maximum 30 V DC @ 2A, Relay SPDT, Form C
Door Lock Power	12V DC @ 0.5A
AUX-IN Port	Yes
AUX-Out Port	30V DC @ 2A, Relay SPDT, Form C

## AUDIO-VISUAL

LED	Yes (Tri Color)
-----	-----------------

## ELECTRICAL

Input Power	PoE+ (IEEE 802.3 af), 12VDC @ 1.8A OR 12 VDC @ 2A Power Adaptor
CPU	ARM Processor, 800MHz

Memory 256MB Flash, 2GB RAM

**PHYSICAL**

Mounting Wall Mount OR Din-Rail Mounting Options  
Dimensions (W x H x D) (mm<sup>3</sup>) 140mm(H) x 78mm(W) x 25mm(D)  
Weight (kg) 0.45 (0.99 lbs.)

**ENVIRONMENTAL**

Humidity 5% to 85% RH Non-Condensing  
Operating Temperature -10°C to + 50°C (32°F to 122°F)

**OTHERS**

System Integration API for Software Integration

**CERTIFICATIONS**

CE, FCC, RoHS and UL

*\*Due to continuous technology upgradations, product specifications are subject to change without notice.*

[info@ampletrails.com](mailto:info@ampletrails.com)

<https://ampletrails.com/cosec-arc-dc200p/biometric-access-control-systems/>