

## Integrated with IP Camera / DVR / Fire Alarm System



**InBio-460**



**IP Camera**

### ➔ Multidoor Access Control - 4 Door

CPU : 32bit MIPS CPU  
 RAM : 32MB, Flash Memory : 128MB  
 Fingerprint Capacity : 3000  
 Card Capacity : 30,000  
 Event buffer : 1,00,000  
 Power / Current : DC 9.6V - 14.4V , Rated Max 1A  
 Wiegand Reader Port : 4ea (26/34 bit Wiegand ,  
 4/8bit for PINRS485)  
 Reader Port : 1no. extended RS485 Port  
 Communication : RS485 , TCP/IP  
 Baud Rate : 38,400bps (recommended) / 9600bps ,  
 19,200 bps , 57,600 bps (selectable)  
 Input Port : 8ea (exit button #1 , exit button #2 ,  
 button #3 , button #4,  
 Door Sensor #1 ,Door Sensor #2 ,  
 Door Sensor#3 , Door Sensor #4)  
 Supports : F12 (RS 485) Fingerprint Reader

#### Features:

- ▶ 256 time Zones, 256 access levels
- ▶ Anti-passback function
- ▶ Interlock function , Linkage function
- ▶ Multi-Card opening function, Remote door opening and closing
- ▶ Real-Time monitoring via web browser
- ▶ Video server integration
- ▶ 4 auxiliary input may be connected to infrared body detectors, fire alarms, smoke detectors etc.
- ▶ 4 auxiliary output may be connected to alarms, cameras, door bells etc.
- ▶ Supports : eSSL 5000 / 7500 for fingerprint registration

#### Connectivity Diagram

