



## iFace 302

### ➔ Multi-biometric Identification Time Attendance and Access Control Terminal

CPU: Multi-Bio CPU 800 MHz  
Memory: 256M Flash, 64M SDRAM  
Camera: High Resolution Infrared Camera  
Display: 4.3" TFT touch screen  
Algorithm Version: Face 7.0, Finger 10.0 version  
Fingerprint Sensor: 500 DPI Optical Sensor  
Fingerprint Capacity: 2000  
Face Capacity: 1200 (1:N), 3000 (1:1)  
Transaction Capacity: 1,00,000  
Inbuilt Proximity Card Reader  
Communication: TCP/IP, RS232/485, Two USB-host  
Access Control: Supports EM Lock, Exit button  
Wiegand Signal: Output  
Power Supply: 12V, 3A  
Verification Speed: ≤2 sec  
Operating Temperature: 0°C - 45°C  
Operating Humidity: 20% - 80%  
Dimension (LxWxT): 193.6 x 146.8 x 111 mm

#### Standard Functions:

- ▶ Self Service Query
- ▶ 9 digit user ID
- ▶ Automatic Status Switch
- ▶ Workcode
- ▶ T9 Input

#### Optional Features:

- ▶ Mifare Card
- ▶ Wi-Fi / Web-server / GPRS
- ▶ Short Message