



AHD-MT- APT-B1- 3.6

➔ Analogue High Definition Camera

Image Sensor : 1/3"
Effect Pixels : PAL:1280(H)×720(V)
Lens installation : 3.6MM MP
Sync : Internal Synchronization
Shutter : 1/53~1/100000s
AGC : AGC/ AGC + Slow shutter
S/N Ratio : >50dB (AGC OFF)
Video output : 1.0Vp-p,75Ω
Resolution : 960P
Minimum Illumination : Color 0.5Lux
(F1.2,50IRE,AGC ON),
B/W : 0.01Lux(F1.2,50IRE,AGC ON)
D/N Switch : Color /Auto
D/N Switch time : 0~255
White Balance : ATW /PUSH/User1/ User 2/
Manual/ANTI CR/PUSH

Mirror : Vertical/ Horizontal /
Vertical + Horizontal /Off
DNR : High/Medium to high/Medium/
Low to medium/Low/Off
OSD : Yes
IR Red : 24 Pieces
IR wavelengths : 850nm
IR Distance : 8-15M
IR ON/OFF : Auto
Power : DC12V±10%(AC24V optional)
Wattage : 2.0W
Operating Temperature : -10°C~50°C
Operating Humidity : <90%
Storage Temperature : -40°C~+60°C
Weight : 500g