



Face



Fingerprint



RFID



Access

MULTI-BIO TIME ATTENDANCE & ACCESS CONTROL SYSTEM

Technical Details:

- Face capacity: 3000
- Fingerprint capacity: 2000
- ID Card capacity: 10,000
- Transaction Storage: 100,000
- CPU : 1.0GHz
- Communication: TCP/IP, RS232/485, USB Host
- Display: 4.3-Inch Capacitive Touch Screen
- Fingerprint Sensor : 500 DPI Optical sensor
- FAR : $\leq 0.0001\%$ FRR : $\leq 1\%$
- Identification speed : < 0.5 sec
- Push Data: Yes
- Wiegand Signal: Output
- Photo ID Access Control Interfaces for: 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm
- Power supply: 12V 3A
- Operating Temperature : $0^{\circ} - 45^{\circ}$
- Operating Humidity: 20%-80%
- Dimensions: 193.6 x 165.2 x 86mm(L x W x T)
- Package Weight: 1.6kg

Special Features:

- High Verification speed
- Advanced and user-friendly UI
- Easy to extend functions and customize client's requirements
- One face template is registered for one user only
- Standard Functions: Automatic Status Switch, Self-Service Query, Work Code, SMS, DST, T9 Input, 9 Digit User ID, Scheduled Bell,
- **Optional** - Battery : 7.4 V, 2000 mAh Backup Battery, Mifare Card, Wi-Fi, 3G GPRS,

Compatibility

- Compatible with Multi Door controllers via weigand
- External Speaker output available (optional)
- External Bulb Output available (optional)
- Support External Printer

Compatible Software & SDK

SmartOffice
Time and Attendance Software

- Smart office suite desktop and web
- Smart office 365 cloud
- SDK for desktop applications

Call Us. +91-9315-4410-53+91-9034-7576-73