



## STANDALONE FINGERPRINT TIME ATTENDANCE AND ACCESS CONTROL SYSTEM

### Technical Details:

- Fingerprints Templates : 10,000
- Transaction Storage : 1,00,000
- Card Capacity : 10,000
- Card Reader : Inbuilt proximity card reader (optional Mifare)
- Communication : TCP/IP, USB, Rs232, RS485 (Optional : Wifi, GPRS, GPRS+GPS)
- Push Data : Yes (Support both static IP and domain server)
- CPU : 800 Mhz 32 bit Microprocessor
- Fingerprint sensor : 500 DPI Optical Sensor
- FAR :  $\leq 0.0001\%$  / FRR :  $\leq 1\%$
- Identification Speed :  $\leq 0.5\text{sec}$
- Algorithm Ver : 10
- Display : 3" Color TFT
- Keypad : Yes
- Schedule Bell/Speaker : Mini Speaker
- Standard Features : Work code, SMS, DLST, Self Service Query, Status Switch
- Power Supply : DC 12 V , 1.5Amps
- Operating Temperature : 0°C to 45°C
- Operating Humidity : 20% - 80%
- Dimension : 210 x 157 x 40mm

### Special Features:

- Wiegand : In & Out both 26 or 34 bit (With or without site code)
- Relay : 12V relay for lock EM lock, Bolt Lock or Strike lock
- Support Fire Alarm : Yes / Door Sensor : Yes
- Anti Pass back : yes / Door Bell : Yes
- Support exit reader : FR-1200, Push Button, KR500
- Battery : Optional

### Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)
- Support External Printer

### Compatible Software & SDK



- Smart office suite desktop and web
- Smart office 365 cloud
- SDK for desktop applications
- Web based Device manager/ Push server using push data. helps developers & integrators
- Supports 3rd party payroll/HRMS/ERP and other applications

Call Us. +91-9315-4410-53+91-9034-7576-73