

SFace900



➔ Multi-Biometric Time Attendance and Access Control System

Face capacity : 1,200 (1:N), 3,000 (1:1)
Fingerprint capacity : 2000 (Optimal 4000)
ID Card capacity : 10,000 (Optional)
Logs capacity : 100,000
Display : 4.3-Inch Touch Screen
Communication : TCP/IP, RS232/485, USB Host
Standard Functions : Automatic Status Switch,
Self-Service Query, Work Code, SMS DST,
T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID
Interfaces for : 3rd Party Electric Lock, Door Sensor,
Exit Button, Alarm
Wiegand Signal : Output
Optional Functions : ID/MiFare Card, Wi-Fi, 3G,
ADMS, 200 mAH Backup Battery
Power Supply :12V 3A
Operating Temperature : 0°C to 45°C

Operating Humidity : 20% - 80%
Dimensions : 195.5x166.5x120mm (LxWxT)
Package Weight : 1.6 kg

Features :

- ▶ 1,200 face and 2,000 fingerprint templates
- ▶ Multi-languages
- ▶ High verification speed
- ▶ Optional battery backup
One face template is registered for one user only
- ▶ Able to detect whether the face is an actual
face or a photo, enhancing the security level of
verification
- ▶ Outside installation (maximum 12,000 lux)