

Made in India

SATATYA CIDR30MVL12CWP 3MP IR Dome Camera with 2.8-12mm Lens







SATATYA CIDR30MVL12CWP 3MP IR Dome Camera with 2.8-12mm Lens


Matrix Project Series IP Cameras are built using superior components such as Sony STARVIS sensor and higher MTF lens to offer unmatched image quality especially during the low light conditions. Powered by True WDR algorithm, these cameras offer consistent image quality even in highly varying lighting conditions. Built in intelligent analytics including Intrusion Detection, Trip Wire, etc. ensure real-time security. Moreover, H.265 compression and Automatic Motion based Frame Rate Reduction save bandwidth and storage up to 50%.



+91- 9315441078



3MP IR Dome Camera with 2.8-12mm Lens



SECURITY SOLUTIONS

TECHNICAL SPECIFICATIONS		
IMAGE SENSOR		
Resolution	3 MP (2048 x 1536)	
	1/2.8" SONY - CMOS 3MP Active Pixel	
	Progressive Scan, Back Illuminated Image sensor	
Sensor Type and Size	(EXMOR Technology - STARVIS Series)	
LENS		
	Colour - 0.01 Lux @F1.2 (AGC ON)	
Minimum Illumination	Monochrome - 0 Lux	
Focal Length	2.8mm-12mm	
Focus Range	0.3m to infinity	
	HFOV: 88°-30°	
	VFOV: 65°-23°	
Field of View (FOV)	DFOV: 117°-38°	
Lens Mount	M14	
Focus	Automatic focus	
Aperture (F#)	F 1.4 – F 2.8	
Iris Type	P Iris	
IR Range	50m	
IR Led Wavelength	850nm	
IR Switching	Auto/ Manual	
AUDIO INTERFACE		
Audio IN	1	
Audio OUT	1	
Two-way Audio	Supported	
Audio Compression	G.726 and G.711	
Alarm IN	Yes	
Alarm OUT	Yes	
HARDWARE SPECIFICATIONS		
SD Card	Up to 512GB	
Camera Adjustment Angle	Pan: 0° to 360°	
	Tilt: 0° to 75°	
	Zoom: 0° to 360°	
IMAGE AND VIDEO		
No of Stream Profiles	4	
	Profile 1: 2048x1536 @30fps (H.264/H.265) Profile 2: D1 @30fps (H.265/H.264)	
	Profile 3: 2048x1536 @5fps (MJPEG)	
Stream Profiles	Profile 4: 720p @30fps (H.265/H.264/MJPEG)	

Customer Care: 1800-258-7747

Made in India



E-mail: Inquiry@MatrixComSec.com

www.MatrixVideoSurveillance.com Call as : +91-9315441053 +91-9315441078



3MP IR Dome Camera with 2.8-12mm Lens



Available Resolutions	2048 x 1536, 1920 x 1080, 720p, D1, VGA, 2CIF, CIF, QCIF
Max Resolution	2048 x 1536
Bitrate	128 kbps-8Mbps
Bitrate Type	CBR, VBR
Video Compression	H.265, H.264, MJPEG
Frame Rate	1-30fps
Shutter Speed	1/25-1/17000 s
Adaptive Streaming	Yes
ONVIF Profiles	S and G
Edge Recording	Yes
Alarm Recording	Pre and Post
Motion Recording	Yes
Video Parameters	Snapshot, Region of Interest (ROI), BLC, Day/Night Settings
Privacy Masks	3
WDR	True WDR (120dB)
SNR	73db
Image Enhancement	Saturation/Contrast/Sharpness/Brightness/Auto Exposure
DNR	2D &3D
Video Analytics	Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Loitering, Missing/ Abandoned Object, Audio Exception, IP Conflict, Network Disconnect, Storage Full, Time Triggered, Alarm In, Object Counting
	EVENTS AND ACTIONS
Upload Image	SD, NAS, FTP
Upload Clip	SD, NAS, FTP
Notifications	E-mail, SMS, TCP
	PROTOCOLS SUPPORTED
Supported protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTCP, RTSP, PPPOE, SMTP, NTP, HTTPS, TLS/SSL, FTP, ICMP, IGMP v2 & v3
Web Viewer	Supported in IE 8.0-11.0, Firefox 15.0-47.0, Chrome 20.0-54.0
Plugins	IE: Matrix ActiveX Chrome: VLC plugin (2.0.4) and Quicktime (7.7.5) Mozilla: VLC plugin (2.0.4) and Quicktime (7.7.5)
-	OPERATING PARAMETERS
Power Supply	12V (DC); 802.3af (PoE)
Power Consumption	<8W
Operating Humidity	<8W Less than 90% RH (non-condensing)
•	

Customer Care: 1800-258-7747

Made in India



E-mail: Inquiry@MatrixComSec.com

www.MatrixVideoSurveillance.com Call as : +97-9315441053 +97-9315441078



3MP IR Dome Camera with 2.8-12mm Lens



SECURITY SOLUTIONS

PHYSICAL PARAMETERS		
Communication interface	10Base-T/100BaseTX Ethernet (RJ-45)	
Weight	1410gm	
Colour	Pantone 7527C	
Dimensions	Φ158 x 134 mm	
Storage	NAS, SD Card	
Certifications	CE, FCC, ROHS, BIS, IP66, IK10, UL	

Customer Care: 1800-258-7747






www.MatrixVideoSurveillance.com Call as : +97-9315441053 +97-9315441078



3MP IR Dome Camera with 2.8-12mm Lens



DIMENSIONS (in mm)



ABOUT MATRIX

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology driven and customer focused organization, is committed to keep pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 1000 system integrators, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.

* Specifications are subject to change without prior notice.

Customer Care: 1800-258-7747





E-mail: Inquiry@MatrixComSec.com

www.MatrixVideoSurveillance.com Call as : +97-9315441053 +97-9315441078