

3MP IR Dome Camera with 3.6mm Lens







#### **SATATYA MIDR30FL36CWP**

3MP IR Dome Camera with 3.6mm Lens

Matrix Professional Series Dome IP Cameras are built using superior components such as Sony STARVIS sensor and higher MTF lens to offer unmatched image quality especially during the low light conditions. Powered by True WDR algorithm, these cameras offer consistent image quality even in highly varying lighting conditions. Built in intelligent analytics including Intrusion Detection, Trip Wire, etc. ensure real-time security. Moreover, H.265 compression and Automatic Motion based Frame Rate Reduction save bandwidth and storage up to 50%.

#### **USP**



SONY STARVIS SENSOR



SMART STREAMING



H.265



ADAPTIVE STREAMING



IVA



TRUE WDR



HIGHER FIELD OF VIEW



NAS

#### **CERTIFICATION**













Customer Care: 1800-258-7747

E-mail: Inquiry@MatrixComSec.com

www.MatrixVideoSurveillance.com

Call as: +91-9315441053 +91-9315441078





3MP IR Dome Camera with 3.6mm Lens



TECHNICAL SPECIFICATIONS IMAGE SENSOR		
	1/2.8" SONY - CMOS 3MP Active Pixel	
	Progressive Scan, Back Illuminated Image sensor	
Sensor Type and Size	(EXMOR Technology - STARVIS Series)	
LENS		
	Colour - 0.01 Lux @ F1.2 (AGC ON)	
Minimum Illumination	Monochrome - 0 Lux	
Focal Length	3.6mm	
Focus Range	0.3m to infinity	
	HFOV - 82°	
	VFOV - 59°	
Field of View (FOV)	DFOV - 111°	
Lens Mount	M12	
Focus	Fixed focus	
Aperture (F#)	F 1.2	
Iris Type	Fixed	
IR Range	30m	
IR Led Wavelength	850nm	
IR Switching	Auto/ Manual	
	AUDIO INTERFACE	
Audio IN	1	
Audio OUT	1	
Two-way Audio	Supported	
Audio Compression	G.726 and G.711	
HARDWARE SPECIFICATIONS		
SD Card	Up to 512GB	
Camera Adjustment Angle	Pan: 0° to 360°	
	Tilt: 0° to 75°	
	Rotation: 0° to 360°	
	IMAGE AND VIDEO	
No of Stream Profiles	4	
	Profile 1: 2048X1536 @30fps (H.264/H.265)	
	Profile 2: D1 @30fps (H.265/H.264)	
Stroom Profiles	Profile 3: 2048x1536@5fps (MJPEG)	
Stream Profiles	Profile 4: 720p @30fps (H.265/H.264/MJPEG)	
Available Resolutions	2048 x 1536, 1920 x 1080, 720p, D1, 2CIF, CIF, QCIF	
Max Resolution	2048 x 1536	

E-mail: Inquiry@MatrixComSec.com

Customer Care: 1800-258-7747



www.MatrixVideoSurveillance.com

Call as : +91-9315441053 +91-9315441078

### 3MP IR Dome Camera with 3.6mm Lens





Bitrate Type CBR, VBR Video Compression H.265, H.264, MJPEG Frame Rate 1-30fps Shutter Speed 1/25-1/17000 Adaptive Streaming ONVIF Profiles Both S and G Edge Recording Yes Alarm Recording Pre and Post Motion Recording Yes Video Parameters Privacy Masks WDR True WDR (120dB) SNR 73db Image Enhancement DNR Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP Video Analytics Video CBR, VBR VIADA H.264, MJPEG H.265, H.265, MJPEG H.265, H.264, MJPEG H.265, H.265, MJPEG H.265, H.264, MJPEG H.265,		
Video CompressionH.265, H.264, MJPEGFrame Rate1-30fpsShutter Speed1/25-1/17000Adaptive StreamingYesONVIF ProfilesBoth S and GEdge RecordingYesAlarm RecordingPre and PostMotion RecordingYesVideo ParametersSnapshot, Region of Interest (ROI), BLC, Day/Night SettingsPrivacy Masks3WDRTrue WDR (120dB)SNR73dbImage EnhancementSaturation/ Contrast/ Sharpness/Brightness/Auto ExposureDNR2D &3DMotion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Frame Rate 1-30fps  Shutter Speed 1/25-1/17000  Adaptive Streaming Yes  ONVIF Profiles Both S and G  Edge Recording Yes  Alarm Recording Pre and Post  Motion Recording Yes  Video Parameters Snapshot, Region of Interest (ROI), BLC, Day/Night Settings  Privacy Masks 3  WDR True WDR (120dB)  SNR 73db  Image Enhancement Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure  DNR 2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Adaptive Streaming ONVIF Profiles Both S and G  Edge Recording Yes  Alarm Recording Pre and Post  Motion Recording Yes  Video Parameters Snapshot, Region of Interest (ROI), BLC, Day/Night Settings Privacy Masks 3  WDR True WDR (120dB) SNR 73db  Image Enhancement DNR 2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
ONVIF Profiles  Edge Recording  Alarm Recording  Pre and Post  Motion Recording  Yes  Video Parameters  Snapshot, Region of Interest (ROI), BLC, Day/Night Settings  Privacy Masks  True WDR (120dB)  SNR  73db  Image Enhancement  DNR  2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Edge Recording Alarm Recording Pre and Post Motion Recording Yes Video Parameters Snapshot, Region of Interest (ROI), BLC, Day/Night Settings Privacy Masks 3 WDR True WDR (120dB) SNR 73db Image Enhancement Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure DNR 2D &3D Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Alarm Recording  Motion Recording  Yes  Video Parameters  Snapshot, Region of Interest (ROI), BLC, Day/Night Settings  Privacy Masks  3  WDR  True WDR (120dB)  SNR  73db  Image Enhancement  Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure  DNR  2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Motion RecordingYesVideo ParametersSnapshot, Region of Interest (ROI), BLC, Day/Night SettingsPrivacy Masks3WDRTrue WDR (120dB)SNR73dbImage EnhancementSaturation/ Contrast/ Sharpness/Brightness/Auto ExposureDNR2D &3DMotion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Video Parameters  Snapshot, Region of Interest (ROI), BLC, Day/Night Settings  Privacy Masks  3  WDR  True WDR (120dB)  SNR  73db  Image Enhancement  Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure  DNR  2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Privacy Masks  3  WDR  True WDR (120dB)  SNR  73db  Image Enhancement  Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure  DNR  2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
WDR True WDR (120dB)  SNR 73db  Image Enhancement Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure  DNR 2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
SNR 73db  Image Enhancement Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure  DNR 2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Image Enhancement         Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure           DNR         2D &3D           Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
DNR 2D &3D  Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Motion/No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
Detection, Object Intrusion/Zone Intrusion, Audio Exception, IP		
EVENTS AND ACTIONS		
Upload Image SD, NAS, FTP		
Upload Clip SD, NAS, FTP		
Notifications E-mail, SMS, TCP		
PROTOCOLS SUPPORTED		
TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTCP, RTSP, PPPOE, SMTP,		
Supported protocols NTP, HTTPS, TLS/SSL, FTP, ICMP, IGMP v2 & v3		
Web Viewer Supported in IE 8.0-11.0, Firefox 15.0-47.0, Chrome 20.0-54.0		
IE: Matrix ActiveX		
Chrome: VLC plugin (2.0.4) and Quicktime (7.7.5)		
Plugins Mozilla: VLC Plugin (2.0.4) and Quicktime (7.7.5)		
OPERATING PARAMETERS		
Power Supply 12V (DC); 802.3af (PoE)		
Power Consumption <5.5W		
Operating Humidity Less than 90% RH (non-condensing)		
Operating Temperature 0°C to 50°C		
Storage Temperature -20°C to 50°C		
PHYSICAL PARAMETERS		
Communication interface 10Base-T/100BaseTX Ethernet (RJ-45)		
Weight 450gm		

E-mail: Inquiry@MatrixComSec.com

Customer Care: 1800-258-7747

Made in India

Ample Trails

www.MatrixVideoSurveillance.com

Call as : +91-9315441053 +91-9315441078




# 3MP IR Dome Camera with 3.6mm Lens



Six M	ATRIX
SECURITY	SOLUTIONS

Colour	Pantone 7527C
Dimensions	110mm x 85mm (Length x Width)
Storage	NAS, SD Card
Certifications	BIS. CE. IP66. FCC Part-15 Class-A. ONVIF S & G. IK10


Customer Care: 1800-258-7747 E-mail: <a href="mailto:lnquiry@MatrixComSec.com">lnquiry@MatrixComSec.com</a> www.MatrixVideoSurveillance.com






Call as : +91-9315441053 +91-9315441078 MATRIX

#### **DIMENSIONS** (in mm)





#### **ABOUT MATRIX**

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology driven and customer focused organization, is committed to keep pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 1000 system integrators, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.

E-mail: Inquiry@MatrixComSec.com

\* Specifications are subject to change without prior notice.

Note: IK10 certificate shall be available from March'20.

Customer Care: 1800-258-7747

Made in India

Ample Trails

www.MatrixVideoSurveillance.com

Call as : +91-9315441053 +91-9315441078