



SC 405

## ➔ Proximity T&A System with Access Control

Card Capacity : 30,000  
 Transaction Storage : 50,000  
 Card Reader : Yes  
 CPU : 32 bit High End Microprocessor  
 FAR : <=0.0001% / FRR : <=1%  
 Identification Speed : <=0.1 sec  
 Display : Color TFT  
 Keypad : 4 x 4 Keypads  
 LED Indicator : Green/Red  
 Schedule Bell/Speaker : Mini Speaker  
 Communication : TCP/IP,USB,RS485  
 Power Supply : 12V DC, 2amps / 3amps  
 Operating Temperature : 0°C to 45°C  
 Operating Humidity : 20% -80%  
 Dimension : 143 x 95.5 x39.5mm  
**Access Control** : Wiegand : In & Out  
 Relay : Inbuilt relay to communicate with Locks,  
 Alarms & Door Sensors

Support Fire Alarm : Yes / Door Sensor ; Yes  
 Anti Passback : Yes / Door Bell : Yes  
 Support exit reader : KR 500E / Exit Button /  
 101 HE,50 time zones, 5 groups, 10 time combinations  
 Battery : No / Card Readers : Yes  
 Communication : No  
 Printer : No  
**Compatibility :**  
 - Compatible with Multi Door controllers via weigand  
 - External Speaker output available (Optional)  
 - External Bulb output available (Optional)  
**Compatible Software & SDK :**  
 - etime tracklite Desktop & Web  
 - SDK for desktop applications  
 - Web based Device Manager/ePush server using  
 Push data. Helps developers & integrators  
 - Supports 3rd Party Payroll/HRMS/ERP  
 and Other applications