

Aiface Orcus



Aiface Orcus

TECHNICAL SPECIFICATIONS

Display : 2.4"@ TFT Color LCD Screen (320*240)

Camera : WDR Binocular Camera @ 1MP

Operation System : Linux

Hardware : CPU: Dual Core@1GHz , RAM: 512MB , ROM: 8GB

Multiple Authentication method : Fingerprint / Face / Card / Password

Fingerprint Template Capacity : 3000

Face Template Capacity : 1500

Card Capacity : 3000

User Capacity : 3000

Transaction Capacity : 1,50,000

**Biometric Authentication Speed : Fingerprint: < 0.5 sec;
Facial Authentication: < 0.35 sec**

Facial Authentication Distance : 30cm to 200cm

**False Acceptance Rate (FAR) % : Visible Light Facial Authentication :
FAR 0.01% , Fingerprint : FAR 0.0001%**

**False Rejection Rate (FRR) % : Visible Light Facial Authentication :
FRR 0.02% , Fingerprint : FRR 0.01%**

**Available RFID Module : Proximity Card@125 kHz (Standard) ,
Mifare Card@13.56 MHz (Optional)**

Communication : TCP/IP, Wi-Fi, USB

**Access Control Interface : Electro Magnetic Lock/ Electric Lock, Door
Sensor, Exit Button**

Power Supply : DC 12V 1.5A

Operating Temperature : -5 C to 45 C

Operating Humidity : 20% to 80% RH (Non-condensing)

Dimensions : 205.20 mm*74.19 mm*33.30 mm (L*W*H)

Supported Software : eTimetracklite Software, eBioServer