



# FHT-TL-537

## FULL HEIGHT TURNSTILE



+91-931 544 1078  
+91-903 475 7673



info@ampletrails.com



www.ampletrails.com

## Parameters

Size (L*W*H)	1400*1300*2230mm
Pass width	600mm
Power	50W
Material	Body $\bar{\delta}$ =1.2mm / fence $\bar{\phi}$ =1.0mm SUS304
Movement	molding full-height turnstile movement
Sensor	Limited sensor
Indicator Light	Dynamic indicator light
Drive Unit	Anti-burn solenoid
Power Supply	24V 150W
Control Unit	Main board
Communication Interface	Dry contact & Rs485
Pass rate	35-50 persons/minute
Temperature	-20°C~+70°C
Humidity	<90% No condensation
IP	IP4X
Environment	Indoor and outdoo

## Functions & Features

- Reasonable and reliable design, low noise, smooth operation and long service life ;
- With function of opening doors automatically under power-off state to meet the need of fire-fighting passage ;
- With functions of anti-tail, anti-reverse pass and so on;
- Card can be set "with memory" or "without memory" functions;
- With automatic reset function, i.e. after having access to the gate, the gate automatically restores to the locked state if not pass within the time set;
- With infrared anti-clip function (anti-clip when gate is open or running);
- Compatible with IC, ID card, scanning and face recognition,etc.



+91-931 544 1078  
+91-903 475 7673



info@ampletrails.com



www.ampletrails.com